



FA 550 dew point sensor - In robust die-cast aluminium housing

The FA 550 is ideal for outdoor dew point measurements or rougher industrial environment



Special features:

- Robust, waterproof die-cast aluminium housing, IP 67
- Alarm relay - limit value adjustable via buttons (max 60 VDC, 0.5 A)
- 4...20 mA analogue output
- Optional: 2 pieces 4 ... 20 mA analogue output e.g. for dew point and temperature
- Extremely stable in the long term
- Quick adaption time
- Pressure-resistant up to 500 bar (optional)
- **NEW:** Modbus-RTU interface
- **NEW:** Ethernet interface (optional)
- **NEW:** Higher resolution of sensor signal due to the improved evaluation electronics
- **NEW:** Sensor diagnosis on site with a portable device or CS Service Software
- **Readable via Modbus:** pressure dew point [° Ctd.], temperature [° C], rel. humidity [% RH], abs. humidity [g/m³], degree of humidity [g/kg], moisture content V/V [ppmV/V], partial vapour pressure [hPa], atmospheric dew point [° Ctd.atm]

APPLICATION:

- Dew point measurement in the compressed air after adsorption dryers/membrane dryers and refrigeration dryers
- Residual moisture measurement / dew point measurement in gases such as: oxygen, nitrogen, argon, hydrogen, natural gas, biogas ...

Easy operation via the keys on the display

The screenshots show the following configuration pages:

- Page 1/3:** Displays the main measurement values: Dew Point (-47.8 °Ctd), Temperature (22.10 °C), Relative Humidity (0.1940 %RH), and Absolute Humidity (0.0378 g/m³).
- Page 2/3:** Shows detailed parameters: Dew Point (0.0321 g/kg), Temperature (50.88 ppm), Pressure (0.0522 hPa), and Dew Point (-47.80 °Ctd).
- Page 3/3:** Displays the alarm configuration for the integrated relay, setting the threshold to -60.00 °Ctd and hysteresis to 2.00.
- Page 4:** Configures the 4...20mA Channel 1, setting the state to 'on', unit to °Ctd, scale 4mA to -80.00°Ctd, and scale 20mA to 20.00°Ctd.
- Page 5:** Configures the 4...20mA Channel 1, setting the state to 'on', unit to g/m³, scale 4mA to 0g/m³, and scale 20mA to 10g/m³.
- Page 6:** IP Address Configuration, showing DHCP checked and static IP 192.168.172.010.
- Page 7:** Pressure Setting, showing Ref.Pressure at 1013.00 hPa and Sys.Pressure at 7500.00 hPa.

The integrated display shows the dew point in big figures as well as further humidity parameters on two more display pages. The arrow key can be used to scroll between the display pages.

The alarm threshold value for the integrated relay can be freely entered via the keys. In addition to the alarm threshold, the hysteresis can also be freely entered.

The 4...20 mA analogue output can be scaled freely or also allocated to one further parameter, e. g. g/m³.

After entering the system pressure of the compressed air system and the reference pressure (atmospheric pressure), the sensor can also calculate back to the atmospheric dew point from the measured pressure dew point if desired.

Example order code FA 550: 0699 0550_A1_B1_C1_D1_E1_F1_G1_H1_I1

Measuring range	
A1	-80...+20 °Ctd. (-112 to 68 °F)
A2	-20...+50 °Ctd. (-4 to 122 °F)
A3	-40...+30 °Ctd. (-40 to 86 °F)
A4	-60...+30 °Ctd. (-76 to 86 °F)
A5	-80...+20 °Ctd. (-112 to 68 °F) (scaling 4...20 mA = -100...+20 °Ctd.)
A6	-80...+20 °Ctd. (-112 to 68 °F) (scaling 4...20 mA = -110...+20 °Ctd.)

Display option	
B1	with integrated display
B2	without display

Option Signal output / Bus connection	
C1	2 x 4 ... 20 mA analogue output (electrically isolated), alarm relay, RS 485 (Modbus-RTU)
C4	1 x 4 ... 20 mA analogue output (not electrically isolated), alarm relay, RS 485 (Modbus-RTU)
C5	Ethernet interface (Modbus / TCP), 1 x 4 ... 20 mA analogue output (not electrically isolated), alarm relay, RS 485 (Modbus-RTU)
C8	M-Bus
C9	Ethernet interface PoE (Power over Ethernet) Modbus / TCP), 1 x 4 ... 20 mA analogue output (not electrically isolated), alarm relay, RS 485 (Modbus-RTU)

Special version analogue output	
D1	No special version
D2	Special version 2...10 V

DESCRIPTION	ORDER NO.	TECHNICAL DATA FA 550
FA 550 Dew point sensor in robust die-cast aluminum housing	0699 0550	Measuring range: -80...20 °Ctd, -60...30 °Ctd, -20...50 °Ctd, or 0...100% RH
Further accessories: Standard measuring chamber up to 16 bar High pressure measuring chamber for compressed air up to 350 bar Stainless steel bypass measuring chamber for dew point measurement in gases under pressure	0699 3390 0699 3590 0699 3290	Accuracy: ± 1 °C at +50...-20 °Ctd ± 2 °C at -20...-50 °Ctd ± 3 °C at -50...-80 °Ctd
Connection cables: Connection cable for probes 5 m with open ends Connection cable for probes 10 m with open ends Ethernet connection cable length 5 m, M12 plug x-coded (8 pin) to RJ 45 plug Ethernet connection cable length 10 m, M12 plug x-coded (8 pin) to RJ 45 plug Power supply in wall housing for max. 2 sensors VA / FA series 5xx, 100-240 VAC, 23 VA, 50-60 Hz / 24 VDC, 0.35 A CS Service Software VA 550 incl. interface cable to PC (USB) and power supply - for configuration / parametrisation VA 550/570 PNG cable screwing - for FA 550, VA 550/570	0553 0108 0553 0109 0553 2503 0553 2504 0554 0110 0554 2007 0553 0552	Pressure range: -1...50 bar, Special version up to 350 bar or 500 bar Power supply: 24 VDC (10...36 VDC) Protection class: IP 67 EMC: In acc. with DIN EN 61326-1 Operating temperature: -20...50 °C Outputs: Modbus-RTU, 4...20 mA active (not electrically isolated), alarm relay (max. 48 VDC, 0.5 A) Standard: Modbus-RTU, 4...20 mA active (not electrically isolated), alarm relay (max. 48 VDC, 0.5 A) Options: See order code
Calibration and adjustment: Precision calibration at -40 °Ctd or 3 °Ctd incl. ISO certificate Additional calibration point freely selectable	0699 3396 0700 7710	Burden: < 500 Ω Material: Die-cast aluminum housing, sensor tube stainless steel 1.4571 Screw-in thread: G 1/2", optional 5/8" UNF, NPT 1/2"